ATLAS PIPE SUPPORTS

Atlas Pipe Supports are used to provide a safe and reliable means to support and level piping systems. The Atlas supports incorporate a unique I-beam stanchion design and constructed with the mechanical integrity to meet the most demanding requirements. Atlas supports isolate the pipe from the support using a fiberglass reinforced plastic (FRP) pad which prevents metal to metal contact. Inspection of the pipeline is easily accomplished by simply removing the U-bolts and lowering the support head.

The Atlas supports are available in a variety of head configurations to accommodate various pipes, valves and flanges. The supports can be mounted on steel, concrete or other foundations using the proper base configuration. Note: Anchor bolts are not provided, follow proper anchoring procedures.

Manufactured to the highest quality standards, Atlas will save both time and labor which will result in increased profitability on your next project.

FEATURES

- AVAILABLE IN SIZES 2" TO 24"
- 6" HEIGHT ADJUSTMENT
- HEIGHTS BUILT TO SPECIFICATION
- SINGLE OR DUAL U-BOLT HEADS
- ADJUSTMENT NUTS EQUIPPED WITH GREASE FITTINGS
- COMMONLY USED ON:
 - + SKID MOUNTED M&R STATIONS
 - + COMPRESSOR STATIONS
 - + ABOVE GROUND LINES
- CUSTOM CONFIGURATIONS AVAILABLE



Pictured above is the Atlas I adjustable pipe support

OPTIONS

- HEAD CONFIGURATION:
 - +120 DEGREE SADDLE
 - + VALVES
 - + FLANGES
- COATINGS:
 - + BARE
 - + PAINTED
 - + GALVANIZED
- BASE PLATE:
 - + NO PLATE
 - + PLATE WITH HOLES
- INSULATING MATERIALS:
 - + FRP



APPALACHIAN ENERGY SOLUTIONS. INC.

ATLAS PIPE SUPPORTS

MATERIALS OF CONSTRUCTION

STANCHION:	ASTM A-36 CARBON STEEL
THREADED ROD:	ASTM A-108, ZINC PLATED
U-BOLTS:	HOT DIPPED GALVANIZED, POLYOLEFIN COATING
NUTS:	HEAVY HEX, ZINC-PLATED WITH GREASE FITTING
BASE PLATE:	ASTM A-36, CARBON STEEL
INSULATOR:	FIBERGLASS REINFORCED PLASTIC (FRP)







