

DENSO BUTYL PRIMER

Butyl Tape Primer

Description

Denso Butyl Primer is a quick drying, solvent based, high-tack primer specifically designed to promote maximum adhesion.

Uses

A fast drying butyl based primer for all surfaces prior to the application of various Denso Butyl tapes.

Features

- Fills surface irregularities for intimate contact of tape compound
- Promotes high adhesion
- Fast drying
- Good penetration characteristics
- Can be brush or spray applied

Application

Prepare surfaces by removing all loose scale, rust or other foreign matter by grit blasting or wire brush. Apply a thin uniform coat of Denso Butyl Primer to clean surface and allow to tack dry. Prime only areas to be wrapped the same day. Reprime if area becomes dirty or wet.



Denso Butyl Primer

PROPERTY SPECIFICATIONS

PROPERTIES	ENGLISH
% Solids	46% by wt.
Viscosity @ 73°F (23°C)	200 cps
VOC	450 g/l
Minimum Application Temperature	25°F
Coverage	245 ft ² /Gal
Color	Blue

COVERAGE:

366 ft² per case - 1 quart containers
(33 m² liters per case - 1.0 liter containers)

980 ft² per case - 1 gallon containers
(90 m² liters per case - 4 liter containers)

PACKAGING:

6 each 1 quart containers per case
(6 each 1.00 liter containers per case)

4 each 1 gallon containers per case
(4 each 4 liter containers per case)

Liberty Sales and Distribution, LLC

2880 Bergey Road, Suite F

Hatfield, PA 19440

Phone: (877) 373-0118

Fax: (888) 850-3787

Email: sales@libertysales.net



DENSO NORTH AMERICA

A Member of Winn & Coales International

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.