
UC T DATA SH DENSO FIBER-WRAP Fiberglass Fabric Outerwrap Used Over Petrolatum Tape Systems Denso Fiber-Wrap is a resin coated, woven fiber-mesh fabric that is .005 inches Description (127 microns) in thickness and exhibits excellent tensile strength. Used as an outerwrap for Denso Petrolatum Tape Systems for straight Uses pipe. Provides additional protection against backfill and soil stress. • Excellent tensile strength **Features** Superior holding force · Provides protection against backfill Provides protection against soil stresses The Denso Fiber-Wrap shall be spirally wrapped using sufficient tension to **Application** wrap over the Denso Petrolatum Tape. Apply using a minimum 1" (25 mm) overlap while pressing firmly onto the Denso Petrolatum Tape.



Denso Fiber-Wrap

Property Specifications	
Properties	Values
Tensile Strength (per 1 inch /25 mm width)	85 lb. min. (38.25 kg)
Thread Count per Inch:	
Warp Threads	20
Fill Threads	10
Thickness	.005 inches (127 microns)
Color	White
Roll Width	4", 6", and 12" (10 mm, 150 mm, and 300 mm)
Roll Length	150 ft (45 m)

Quantity Estimates				
Tape Width	Rolls*/Coverage withCase1" (25 mm) Overlap		Coverage with 50% Overlap	
4" (100 mm)	6	225 ft ² /case (21 m ² /case)	150 ft²/case (14 m²/case)	
6" (150 mm)	4	250 ft²/case (23 m²/case)	150 ft²/case (14 m²/case)	
12" (200 mm)	2	825 ft²/case (77 m²/case)	150 ft ² /case (14 m ² /case)	



A Member of Winn & Coales International

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.