

DENSO POLY-WRAP

High Performance Outerwrap and Compression Film

Description

Denso Poly-Wrap is a 200 gauge (2 mil) a compression film wrap made from high performance metallocene resins.

Uses

Compression Film for

- Denso Glass Outerwraps
- Denso Bore-Wrap

Protective Layer for

- Denso Petrolatum Tape Systems

Features

- Superior holding force
- Excellent prestretch with no film breaks
- Aggressive cling to self
- Uses maximum performance metallocene resins
- Excellent conformability

Application

The Poly-Wrap shall be spirally wrapped using sufficient tension to wrap over Denso Glass Outerwraps, Denso Bore-Wrap, and Denso Petrolatum Tape Systems.

Packaging

Roll Width	Roll Length	Rolls*/ Case	Coverage with 50% Overlap
in.	ft.	ea.	ea.
4" (100 mm)	500 feet (150 m)	6	550 ft ² /case (51 m ² /case)
6" (150 mm)	500 feet (150 m)	4	550 ft ² /case (51 m ² /case)
12" (300 mm)	500 feet (150 m)	2	550 ft ² /case (51 m ² /case)



TECHNICAL DATA SHEET

Tech Data

Properties	Imperial	Metric
Yield	~ 15,000 sq. in/lb	~ 21.3 sq. m/kg
Ultimate Tensile MD (ASTM D882)	~ 6,600 psi	~ 45,507 MPa
Ultimate Tensile TD (ASTM D882)	~ 4,150 psi	~ 28,614 MPa
Elongation at Break MD (ASTM D882)	~ 300%	~ 300%
Elongation at Break TD (ASTM D882)	~ 515%	~ 515%
Thickness	2.0 mils	50.8 microns



DENSO, INC.

LIBERTY SALES & DISTRIBUTION, LLC



PHONE: 877-373-0118

FAX: 888-850-3787

EMAIL: sales@libertysales.net

WEB: www.libertysales.net

**A Member of Winn
& Coales International**

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.