



# **EXPLORING ELECTRODES**

## ***For High And Low Voltage Holiday Detectors***



### ***Types:***

- ***Full Circle Spring***
- ***Half Circle Spring***
- ***Silicone-Rubber Brush***
- ***Wire Brush***
- ***Sponge***
- ***Internal Silicone-Rubber Disk***
- ***Internal Sponge Disk***

***Types:***  
***Internal Sponge  
Disk and Custom  
Electrodes available.***

*Distributed by:*

**Liberty Sales & Distribution**

Phone: (877) 373-0118

Email: [sales@libertysales.net](mailto:sales@libertysales.net)

Web: [www.libertysales.net](http://www.libertysales.net)



# TINKER & RASOR

## PRODUCT DATA SHEET | EXPLORING ELECTRODES

### FEATURES:

- Full & Half Circle electrodes roll down pipe.
- Square spring gives closer contact to coating
- Spring made of galvanized steel
- Half circle springs have 190-degree arc
- Silicone-rubber is made of conductive material with very low resistivity
- Wire brushes are crimped stainless steel

### CONSTRUCTION:

- Full Circle Spring electrodes cut to pipe diameter. 2" - up to large diameters avail.
- Galvanized steel for corrosion resistance.
- Conductive silicone-rubber used in couplers, with high grade lubricant for years of use

### APPLICATIONS:

- Full circle and half circle springs used with T&R high voltage holiday detectors, to inspect pipeline coatings in plant or field.
- Silicone-Rubber brush used to inspect welds tanks, or other conductive substrates
- Wire brush used on coatings with irregular surfaces or joints, fittings, etc.

### SPONGE ELECTRODES

The Models M/1 and M1/AC low voltage holiday detectors use a cellulose sponge suitable for rapid wetting.

Sponge should be damp but not dripping when used.

Sponge ships compressed and must be wet to get to full size.

Tinker & Rasor exploring electrodes are designed to provide the user with a method of maintaining close, intimate contact with the coating.

**WARRANTY: 90 Days**, parts and labor

## EXTERNAL ELECTRODES


16" Silicone-Rubber Brush



6" Wire Brush



8" Sponge Electrode



Full Circle Spring (FCE)



Compax Connector



Half Circle Spring (HCE)



24" Custom Sponge Electrode



## HIGH VOLTAGE INTERNAL ELECTRODES

### ELECTRODE KIT INCLUDES:

- Electrode disc (sized to pipe)
- 093-010 Adapter kit
- 005-036 Plug, cable conn.
- 440-type Cable (length = pipe length + 8')
- 009-006 Adapter, powerpak (required for AP/W)



### OPTIONAL:

- 052-001 Roller assembly, single (10"+)
- 052-002 Roller assembly, double (16"+)
- Lance Handle not included. Recommended to use 1/2" PVC

Double Discs available

## LOW VOLTAGE INTERNAL ELECTRODES

### ELECTRODE KIT INCLUDES:

- Electrode disc (sized to pipe)
- 093-009 Adapter kit
- Cable (to length)



Double Discs available