

Issue date: 11/26/2024

Product name: 290 EPOXY PRIMER 0.5PT PART B
Product type/ Epoxy Hardener
Recommended use:
Restriction of Use: None identified
Company address:
 Henkel Corporation
 One Henkel Way
 Rockv Hill, Connecticut 06067

Internet: www.henkeln.com

DANGER: H302 - HARMFUL IF SWALLOWED.
H314 - CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY ORAL	4
SKIN CORROSION	1
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1

P261 - Avoid breathing mist/vapours.
P264 - Wash affected area thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves, clothing, eye and face protection.
P301+P312+P330 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing.
P304+P340+P310 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P405 - Store locked up.
P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Other hazards Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
benzyl alcohol	100-51-6	30 - 60
Formaldehyde, polymer with benzenamine, hydrogenated	135108-88-2	30 - 60
4,4'-Methylenebis(cyclohexylamine)	1761-71-3	5 - 10
salicylic acid	69-72-7	5 - 10

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

Non hazardous components

Actual concentration or concentration range is withheld as a trade secret

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation:	If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	Rinse with running water and soap. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Thoroughly clean shoes before reuse. Discard any shoes or clothing items that cannot be decontaminated. If symptoms develop and persist, get medical attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical attention immediately.
Ingestion:	Seek immediate medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.
Most important symptoms and effects (acute and delayed):	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
Indication of any immediate medical attention / special treatment needed:	Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Improper extinguishing agents:	Not available.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Keep unnecessary personnel away.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. In case of fire, keep containers cool with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products:

Oxides of carbon. Oxides of nitrogen. Phenolics. Acrolein. Toxic fumes.
Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Do not allow product to enter sewer or waterways.

Clean-up methods:

Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed. See Section 8 of the SDS for Personal Protective Equipment.

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame. Store in original container until ready to use. Store away from incompatible materials identified in section 10.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
benzyl alcohol	None	None	10 ppm (44.20 mg/m3) TWA	None

Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	green
Odor:	Amine
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Density/Relative density:	1.64 at 20 °C (68°F)
Relative vapor density:	Not available.
Flash point:	> 103.89 °C (> 219°F) Pensky Martens closed cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.

Solubility:	Not miscible Water
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	0 % (EPA Method 24) (estimated)
Dynamic viscosity:	7,000 - 15,000 cp
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Phenolics. Acrolein. Toxic fumes. Irritating vapors.
Incompatible materials:	Keep away from oxidizing agents, strongly alkaline materials, and strongly acidic materials in order to avoid exothermic reactions.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Mists, vapors or liquid may cause severe irritation or burns.
Skin contact:	Causes skin burns. May cause allergic skin reaction.
Eye contact:	Causes serious eye damage.
Ingestion:	If ingested, severe burns of the mouth and throat may occur, as well as perforation of the esophagus and the stomach.

Hazardous Component(s)	LD50s and LC50s
benzyl alcohol	Oral LD50 (Mouse) = 1,580 mg/kg Oral LD50 (Rat) = 1,230 - 3,100 mg/kg Oral LD50 (Rabbit) = 1,940 mg/kg Oral LD50 (Rat) = 3,100 mg/kg Dermal LD50 (Rabbit) = 2,000 mg/kg Inhalation LC50 (Rat, 4 h) = 8.8 mg/l Inhalation LC50 (Rat, 4 h) = > 4,178 mg/l
Formaldehyde, polymer with benzenamine, hydrogenated	None
4,4'-Methylenebis(cyclohexylamine)	None
salicylic acid	Oral LD50 (Rat) = 891 mg/kg Oral LD50 (Mouse) = 480 mg/kg Dermal LD50 (Rat) = > 2 g/kg

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
benzyl alcohol	Corrosive Irritant	Allergen	Central nervous system
Formaldehyde, polymer with benzenamine, hydrogenated			
4,4'-Methylenebis(cyclohexylamine)	Irritant	Allergen	
salicylic acid	Irritant		

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
benzyl alcohol	No	No	No
Formaldehyde, polymer with benzenamine, hydrogenated	No	No	No
4,4'-Methylenebis(cyclohexylamine)	No	No	No
salicylic acid	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Amines, liquid, corrosive, n.o.s. (Formaldehyde, polymer with benzenamine, hydrogenated, 4,4'-methylenebis(cyclohexylamine))

Hazard class or division:

8

Identification number:

UN 2735

Packing group:

II

International Air Transportation (ICAO/IATA)

Proper shipping name:

Amines, liquid, corrosive, n.o.s. (Formaldehyde, polymer with benzenamine, hydrogenated, 4,4'-methylenebis(cyclohexylamine))

Hazard class or division:

8

Identification number:

UN 2735

Packing group:

II

Water Transportation (IMO/IMDG)

Proper shipping name:

AMINES, LIQUID, CORROSIVE, N.O.S. (Formaldehyde, polymer with benzenamine, hydrogenated, 4,4'-methylenebis(cyclohexylamine))

Hazard class or division:

8

Identification number:

UN 2735

Packing group:

II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification:

None above reporting de minimis

CERCLA/SARA Section 302 EHS:

None above reporting de minimis.

CERCLA/SARA Section 311/312:

Please refer to the GHS classification in Section 2

CERCLA/SARA Section 313:

None above reporting de minimis.

California Proposition 65:

No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: First issue.

Prepared by:

Product Safety and Regulatory Affairs

Issue date:

11/26/2024

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.