

We make a material difference

SAFETY DATA SHEET

1. Identification

Product identifier Tapecoat High Temperature Butyl Tapes

Other means of identification

Synonyms Tapecoat 6025HT, Tapecoat HT/MB

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Chase Corporation - Tapecoat Division

Address 1527 Lyons Street Evanston, IL 60201

United States

Telephone General Assistance 800 543-3458

E-mail info@chasecorp.com

Emergency phone number Chemtrec (US - 24 hrs) 800 424-9300

Chemtrec (INTL - 24 hrs) 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Kaolin Clay		1332-58-7	10 - < 20

Chemical name	Common name and synonyms	CAS number	%
Talc (powder)		14807-96-6	10 - < 20
Zinc Oxide		1314-13-2	1 - < 3
Other components below reporta	ble levels		70 - < 80

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eve contact Rinse with water. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantDirect contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighters
Fire-fighting

Use water spray to cool unopened containers.

equipment/instructions

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Kaolin Clay (CAS 1332-58-7)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Zinc Oxide (CAS 1314-13-2)	PEL	5 mg/m3	Fume.
ŕ		5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	Form
Talc (powder) (CAS 14807-96-6)	TWA	0.3 mg/m3	Total dust.
,		0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Va	llues		
Components	Туре	Value	Form
Kaolin Clay (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Talc (powder) (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Zinc Oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to C	hemical Hazards		
Components	Туре	Value	Form
Kaolin Clay (CAS 1332-58-7)	TWA	5 mg/m3	Respirable.
ŕ		10 mg/m3	Total
Talc (powder) (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
Zinc Oxide (CAS 1314-13-2)	Ceiling	15 mg/m3	Dust.
•	STEL	10 mg/m3	Fume.
	TWA	5 mg/m3	Fume.
		5 mg/m3	Dust.

No biological exposure limits noted for the ingredient(s).

Biological limit values

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Solid. Tape.

Color Various film colors, black adhesive

Odor Slight.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

> 842.0 °F (> 450.0 °C) Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

Explosive limit - lower (%) Explosive limit - upper (%)

Not available. Not available. Not available.

Vapor pressure Vapor density Not available. Relative density Not available.

Solubility(ies)

Insoluble Solubility (water) Partition coefficient Not available.

(n-octanol/water)

> 842 °F (> 450 °C) **Auto-ignition temperature**

Decomposition temperature Not available. Not available. Viscosity

Other information

Density 1.00 - 1.20 g/cm3

Specific gravity 1 - 1.2VOC (Weight %) 0 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Avoid temperatures exceeding the flash point. Contact with incompatible materials. Conditions to avoid

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard. Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Material name: Tapecoat High Temperature Butyl Tapes 995 Version #: 01 Issue date: 05-05-2015

Product	Species	Test Results
Tapecoat High Temperature Buty	Tapes (CAS Mixture)	
Acute		
Dermal		
LD50	Rat	42517.0078 mg/kg estimated
Inhalation		
LC50	Mouse	506.6667 mg/l, 4 Hours estimated
Oral		
LD50	Rat	42517.0078 mg/kg estimated
Other		
LD50	Rat	20931.4492 mg/kg estimated
Components	Species	Test Results
Kaolin Clay (CAS 1332-58-7)		
Acute		
Dermal		
LD50	Rat	> 5000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
Zinc Oxide (CAS 1314-13-2)		
Acute		
Inhalation		
LC50	Mouse	> 5.7 mg/l, 4 Hours
Oral		
LD50	Mouse	7950 mg/kg
	Rat	> 5 g/kg
Other		
LD50	Rat	240 mg/kg
	be based on additional component data	
Skin corrosion/irritation	Prolonged skin contact may cause t	
Serious eye damage/eye irritation	Direct contact with eyes may cause	temporary irritation.
Respiratory or skin sensitizatio		
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to caus	se skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be	a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Talc (powder) (CAS 14807-96-6) 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species Test Results

Tapecoat High Temperature Butyl Tapes (CAS Mixture)

Aquatic

Fish LC50 Fish 39843.5117 mg/l, 96 hours estimated

Components Species Test Results

Zinc Oxide (CAS 1314-13-2)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 2246 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential Not available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Not applicable.

15. Regulatory information

US federal regulations One or more components are not listed on TSCA.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Zinc Oxide (CAS 1314-13-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Material name: Tapecoat High Temperature Butyl Tapes 995 Version #: 01 Issue date: 05-05-2015

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Zinc Oxide	1314-13-2	1 - < 3	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Kaolin Clay (CAS 1332-58-7) Talc (powder) (CAS 14807-96-6) Zinc Oxide (CAS 1314-13-2)

US. New Jersey Worker and Community Right-to-Know Act

Kaolin Clay (CAS 1332-58-7) Talc (powder) (CAS 14807-96-6) Zinc Oxide (CAS 1314-13-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Kaolin Clay (CAS 1332-58-7) Talc (powder) (CAS 14807-96-6) Zinc Oxide (CAS 1314-13-2)

US. Rhode Island RTK

Zinc Oxide (CAS 1314-13-2)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-05-2015

Version # 01

HMIS® ratings Health: 0

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 0

Flammability: 0 Instability: 0

Disclaimer The information offered in this data sheet is designed only as guidance for the safe use, storage

and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only.

No warranty, expressed or implied is made.