Tapecoat Flangecoat

Chase Corporation - Tapecoat Division

Chemwatch: **32202-40**
Version No: **2.1**
Safety Data Sheet according to OSHA HazCom Standard (2024) requirements

Initial Date: **28/08/2026**
Revision Date: **31/08/2026**
Print Date: **03/11/2026**
S.GHS.USA.EN.E.B

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Tapecoat Flangecoat
Synonyms	Not Available
Chemical formula	Not Applicable
Other means of identification	FLGCT

Recommended use of the chemical and restrictions on use

Relevant identified uses	Use according to manufacturer's directions.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	**Chase Corporation - Tapecoat Division**
Address	1527 Lyons Street, Evanston 60201 IL United States of America
Telephone	1 800 543-3458
Fax	Not Available
Website	info@chasecorp.com
Email	Not Available

Emergency phone number

Association / Organisation	**Chemtrec**
Emergency telephone number(s)	**1-800-424-9300 (US)**
Other emergency telephone number(s)	**(+1)703-527-3887 (outside the US)**

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

Classification	Non hazardous

Label elements

Hazard pictogram(s)	Not Applicable
SIGNAL WORD	**NOT APPLICABLE**

Hazard statement(s)

Not Applicable

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

No further product hazard information.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
14807-96-6	40-50	talc
8042-47-5	30-40	white mineral oil (petroleum)
9003-27-4	1-10	isobutylene homopolymer
62258-49-5	<5	alpha-methylstyrene/ amylene/ piperylene copolymer
112945-52-5	<1	silica amorphous, fumed, crystalline free
16389-88-1	<1	dolomite
1318-59-8	<1	chlorite
546-93-0	<1	magnesium carbonate
8029-10-5	<1	coal, anthracite
Not Available	<1	proprietary ingredients
Not Available	Balance	Ingredients determined not to be hazardous

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: • Immediately flush body and clothes with large amounts of water, using safety shower if available. • Quickly remove all contaminated clothing, including footwear. • Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. • Transport to hospital, or doctor.
Inhalation	• If fumes or combustion products are inhaled remove from contaminated area. • Lay patient down. Keep warm and rested. • Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. • Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. • Transport to hospital, or doctor, without delay.
Ingestion	• Immediately give a glass of water. • First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. • If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

Special hazards arising from the substance or mixture

Fire Incompatibility	• Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting	• Alert Fire Brigade and tell them location and nature of hazard. • Wear breathing apparatus plus protective gloves. • Prevent, by any means available, spillage from entering drains or water courses.

	• Use water delivered as a fine spray to control fire and cool adjacent area. • **DO NOT** approach containers suspected to be hot. • Cool fire exposed containers with water spray from a protected location.
Fire/Explosion Hazard	• When silica dust is dispersed in air, firefighters should wear inhalation protection as hazardous substances from the fire may be adsorbed on the silica particles. • When heated to extreme temperatures, (>1700 deg.C) amorphous silica can fuse. Combustible. Will burn if ignited. Combustion products include: • carbon monoxide (CO) • carbon dioxide (CO_2) silicon dioxide (SiO_2) metal oxides • other pyrolysis products typical of burning organic material. May emit poisonous fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	• Clean up all spills immediately. • Avoid contact with skin and eyes. • Wear impervious gloves and safety goggles. • Trowel up/scrape up. • Place spilled material in clean, dry, sealed container. • Flush spill area with water.
Major Spills	• Clear area of personnel and move upwind. • Alert Fire Brigade and tell them location and nature of hazard. • Wear full body protective clothing with breathing apparatus. • Prevent, by all means available, spillage from entering drains or water courses. • Consider evacuation (or protect in place). • No smoking, naked lights or ignition sources.

Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	• Avoid skin contact, including inhalation. • Wear protective clothing when risk of exposure occurs. • Use in a well-ventilated area. • Prevent concentration in hollows and sumps. • **DO NOT** enter confined spaces until atmosphere has been checked. • **DO NOT** allow material to come in direct contact with human skin or eyes.
Other information	• Store in original containers. • Keep containers securely sealed. • No smoking, naked lights or ignition sources. • Store in a cool, dry, well-ventilated area. • Store away from incompatible materials and foodstuff containers. • Protect containers against physical damage and check regularly for leaks.

Conditions for safe storage, including any incompatibilities

Suitable container	• Metal can or drum • Packaging as recommended by manufacturer. • Check all containers are clearly labelled and free from leaks.
Storage incompatibility	The substance may be or contains a "metalloid" The following elements are considered to be metalloids; boron,silicon, germanium, arsenic, antimony, tellurium and (possibly) polonium The electronegativities and ionisation energies of the metalloids are between those of the metals and nonmetals, so the metalloids exhibit characteristics of both classes. The reactivity of the metalloids depends on the element with which they are reacting. For example, boron acts as a nonmetal when reacting with sodium yet as a metal when reacting with fluorine. Unlike most metals, most metalloids are amphoteric- that is they can act as both an acid and a base. For instance, arsenic forms not only salts such as arsenic halides, by the reaction with certain strong acid, but it also forms arsenites by reactions with strong bases. Most metalloids have a multiplicity of oxidation states or valences. · **CARE**: Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire. · Oil leaks in a pressurized circuit may result in a fine flammable spray (the lower flammability limit for oil mist is reached for a concentration of about 45 g/m3 · Autoignition temperatures may be significantly lower under particular conditions (slow oxidation on finely divided materials.. • Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes

US OSHA Permissible Exposure Limits (PELs) Table Z-3	talc	Silicates (less than 1% crystalline silica): Soapstone	20 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	talc	Silicates (less than 1% crystalline silica): Talc (not containing asbestos)	20 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	talc	Silicates (less than 1% crystalline silica): Talc (containing asbestos)	Not Available	Not Available	Not Available	Use asbestos limit
US ACGIH Threshold Limit Values (TLV)	talc	Talc: Containing no asbestos fibers (Respirable particulate matter)	2 mg/m3	Not Available	Not Available	A4
US ACGIH Threshold Limit Values (TLV)	talc	Talc: Containing asbestos fibers	Not Available	Not Available	Not Available	A1
US NIOSH Recommended Exposure Limits (RELs)	talc	Talc (containing no asbestos and less than 1% quartz) - respirable	2 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	talc	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	talc	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	white mineral oil (petroleum)	Oil mist, mineral	5 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	white mineral oil (petroleum)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined (Inhalable particulate matter)	5 mg/m3	Not Available	Not Available	A4
US ACGIH Threshold Limit Values (TLV)	isobutylene homopolymer	Butenes, all isomers	250 ppm	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	alpha-methylstyrene/ amylene/ piperylene copolymer	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	alpha-methylstyrene/ amylene/ piperylene copolymer	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	alpha-methylstyrene/ amylene/ piperylene copolymer	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	alpha-methylstyrene/ amylene/ piperylene copolymer	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	alpha-methylstyrene/ amylene/ piperylene copolymer	Particulates not otherwise regulated	Not Available	Not Available	Not Available	See Appendix D - Substances with No Established RELs
US OSHA Permissible Exposure Limits (PELs) Table Z-1	silica amorphous, fumed, crystalline free	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	silica amorphous, fumed, crystalline free	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica amorphous, fumed, crystalline free	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica amorphous, fumed, crystalline free	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica amorphous, fumed, crystalline free	Particulates not otherwise regulated	Not Available	Not Available	Not Available	See Appendix D - Substances with No Established RELs
US OSHA Permissible Exposure Limits (PELs) Table Z-1	chlorite	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	chlorite	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	chlorite	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	chlorite	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	chlorite	Particulates not otherwise regulated	Not Available	Not Available	Not Available	See Appendix D - Substances with No Established RELs
US OSHA Permissible Exposure Limits (PELs) Table Z-1	magnesium carbonate	Magnesite- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	magnesium carbonate	Magnesite- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available

US NIOSH Recommended Exposure Limits (RELs)	magnesium carbonate	Magnesite - total	10 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	magnesium carbonate	Magnesite - respirable	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	magnesium carbonate	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	magnesium carbonate	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	coal, anthracite	Coal dust - Anthracite (Respirable particulate matter)	0.4 mg/m3	Not Available	Not Available	A4
US OSHA Permissible Exposure Limits (PELs) Table Z-1	coal, anthracite	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	coal, anthracite	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	coal, anthracite	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	coal, anthracite	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	coal, anthracite	Particulates not otherwise regulated	Not Available	Not Available	Not Available	See Appendix D - Substances with No Established RELs

EMERGENCY LIMITS

Ingredient	TEEL-1	TEEL-2	TEEL-3
white mineral oil (petroleum)	140 mg/m3	1,500 mg/m3	8,900 mg/m3
silica amorphous, fumed, crystalline free	18 mg/m3	100 mg/m3	630 mg/m3
magnesium carbonate	45 mg/m3	260 mg/m3	1,600 mg/m3

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
Individual protection measures, such as personal protective equipment	
Eye and face protection	• Safety glasses with side shields • Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] • Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.
Skin protection	See Hand protection below
Hands/feet protection	• Wear chemical protective gloves, e.g. PVC. • Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	• Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent] • Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. [AS/NZS 1715 or national equivalent] • Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely. • Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. • Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood. • Overalls. • P.V.C apron. • Barrier cream. • Skin cleansing cream.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Gray paste with characteristic odour

Physical state	Non Slump Paste	**Relative density (Water = 1)**	~1.87
Odour	Not Available	**Partition coefficient n-octanol / water**	Not Available
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	>450
pH (as supplied)	Not Available	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	Not Available	**Viscosity (mm2/s)**	Not Available
Initial boiling point and boiling range (°C)	360	**Molecular weight (g/mol)**	Not Applicable
Flash point (°C)	>232	**Taste**	Not Available
Evaporation rate	Not Available	**Explosive properties**	Not Available
Flammability	Not Applicable	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	Not Available	**Surface Tension (dyn/cm or mN/m)**	Not Available
Lower Explosive Limit (%)	Not Available	**Volatile Component (%vol)**	~8.3
Vapour pressure (kPa)	Not Available	**Gas group**	Not Available
Solubility in water	Not Available	**pH as a solution (1%)**	Not Available
Vapour density (Air = 1)	Not Available	**Total VOC %w/w**	Not Available
Heat of Combustion (kJ/g)	Not Available	**Ignition Distance (cm)**	Not Available
Flame Height (cm)	Not Available	**Flame Duration (s)**	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	**Enclosed Space Ignition Deflagration Density (g/m3)**	Not Available
Nanoform Solubility	Not Available	**Nanoform Particle Characteristics**	Not Available
Particle Size	Not Available		

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	There is strong evidence to suggest that this material can cause, if inhaled once, very serious, irreversible damage of organs. The material is not classified as causing respiratory irritation under Regulation (EC) No 1272/2008 (CLP), as amended. Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be implemented in an occupational setting. Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs. Inhalation of dusts, generated by the material, during the course of normal handling, may be harmful.
Ingestion	There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. The material is not expected to produce harmful effects following ingestion based on the available information. However, the material may still cause adverse health effects following ingestion, particularly in individuals with pre-existing organ damage (e.g. liver or kidney impairment). Gastrointestinal discomfort may occur and may result in nausea and vomiting. In an occupational setting, ingestion of incidental quantities should be avoided, and good hygiene practices should be followed to prevent ingestion.

Skin Contact	There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The liquid may be miscible with fats or oils and may degrease the skin, potentially producing a non-allergic contact dermatitis. The material is not classified as a skin irritant under Regulation (EC) No 1272/2008 (CLP), as amended. Irritation and skin reactions are possible with sensitive skin Open cuts, abraded or irritated skin should not be exposed to this material The material may accentuate any pre-existing dermatitis condition Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the material is not classified as an eye irritant under Regulation (EC) No 1272/2008 (CLP), as amended, direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	There is sufficient evidence to suggest that this material directly causes cancer in humans. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Tapecoat Flangecoat	TOXICITY	IRRITATION
	Not Available	Not Available

talc	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg [1]	Eye: no adverse effect observed (not irritating) [1]
	Inhalation (Rat) LC50: >2.1 mg/l4h [1]	Skin (Human): 300ug/3D - Mild
	Oral (Rat) LD50: >5000 mg/kg [1]	Skin: no adverse effect observed (not irritating) [1]

white mineral oil (petroleum)	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg [1]	Eye: no adverse effect observed (not irritating) [1]
	Inhalation (Rat) LC50: >4.5 mg/l4h [1]	Skin: no adverse effect observed (not irritating) [1]
	Oral (Rat) LD50: >5000 mg/kg [2]	

isobutylene homopolymer	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg [1]	Eye: no adverse effect observed (not irritating) [1]
	Oral (Rat) LD50: >2000 mg/kg [1]	Skin: no adverse effect observed (not irritating) [1]

alpha-methylstyrene/ amylene/ piperylene copolymer	TOXICITY	IRRITATION
	Not Available	Not Available

silica amorphous, fumed, crystalline free	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >5000 mg/kg [2]	Not Available
	Oral (Rat) LD50: 3160 mg/kg [2]	

dolomite	TOXICITY	IRRITATION
	Not Available	Not Available

chlorite	TOXICITY	IRRITATION
	Not Available	Not Available

magnesium carbonate	TOXICITY	IRRITATION
	Oral (Rat) LD50: >2000 mg/kg [1]	Eye: no adverse effect observed (not irritating) [1]
		Skin: no adverse effect observed (not irritating) [1]

coal, anthracite	TOXICITY	IRRITATION
	Not Available	Not Available

Legend:	***1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances***

silica amorphous, fumed, crystalline free	For silica amorphous: Derived No Adverse Effects Level (NOAEL) in the range of 1000 mg/kg/d. In humans, synthetic amorphous silica (SAS) is essentially non-toxic by mouth, skin or eyes, and by inhalation. Epidemiology studies show little evidence of adverse health effects due to SAS. Repeated exposure (without personal protection) may cause mechanical irritation of the eye and drying/cracking of the skin. When experimental animals inhale synthetic amorphous silica (SAS) dust, it dissolves in the lung fluid and is rapidly eliminated. If swallowed, the vast majority of SAS is excreted in the faeces and there is little accumulation in the body. Following absorption across the gut, SAS is eliminated via urine without modification in animals and humans. SAS is not expected to be broken down (metabolised) in mammals. After ingestion, there is limited accumulation of SAS in body tissues and rapid elimination occurs. Intestinal absorption has not been calculated, but appears to be insignificant in animals and humans. SASs injected subcutaneously are subjected to rapid dissolution and removal. There is no indication of metabolism of SAS in animals or humans based on chemical structure and available data. In contrast to crystalline silica, SAS is soluble in physiological media and the soluble chemical species that are formed are eliminated via the urinary tract without modification. Both the mammalian and environmental toxicology of SASs are significantly influenced by the physical and chemical properties, particularly those of solubility and particle size. SAS has no acute intrinsic toxicity by inhalation. Adverse effects, including suffocation, that have been reported were caused by the presence of high numbers of respirable particles generated to meet the required test atmosphere. These results are not representative of exposure to commercial SASs and should not be used for human risk assessment. Though repeated exposure of the skin may cause dryness and cracking, SAS is not a skin or eye irritant, and it is not a sensitiser. Repeated-dose and chronic toxicity studies confirm the absence of toxicity when SAS is swallowed or upon skin contact. Long-term inhalation of SAS caused some adverse effects in animals (increases in lung inflammation, cell injury and lung collagen content), all of which subsided after exposure. Numerous repeated-dose, subchronic and chronic inhalation toxicity studies have been conducted with SAS in a number of species, at airborne concentrations ranging from 0.5 mg/m3 to 150 mg/m3. Lowest-observed adverse effect levels (LOAELs) were typically in the range

	of 1 to 50 mg/m3. When available, the no-observed adverse effect levels (NOAELs) were between 0.5 and 10 mg/m3. The difference in values may be explained by different particle size, and therefore the number of particles administered per unit dose. In general, as particle size decreases so does the NOAEL/LOAEL. Neither inhalation nor oral administration caused neoplasms (tumours). SAS is not mutagenic in vitro. No genotoxicity was detected in in vivo assays. SAS does not impair development of the foetus. Fertility was not specifically studied, but the reproductive organs in long-term studies were not affected. For Synthetic Amorphous Silica (SAS) Repeated dose toxicity Oral (rat), 2 weeks to 6 months, no significant treatment-related adverse effects at doses of up to 8% silica in the diet. Inhalation (rat), 13 weeks, Lowest Observed Effect Level (LOEL) =1.3 mg/m3 based on mild reversible effects in the lungs. Inhalation (rat), 90 days, LOEL = 1 mg/m3 based on reversible effects in the lungs and effects in the nasal cavity. For silane treated synthetic amorphous silica: Repeated dose toxicity: oral (rat), 28-d, diet, no significant treatment-related adverse effects at the doses tested. There is no evidence of cancer or other long-term respiratory health effects (for example, silicosis) in workers employed in the manufacture of SAS. Respiratory symptoms in SAS workers have been shown to correlate with smoking but not with SAS exposure, while serial pulmonary function values and chest radiographs are not adversely affected by long-term exposure to SAS.
talc	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. The overuse of talc in nursing infants has resulted in respiratory damage causing fluid in the lungs and lung inflammation which may lead to death within hours of inhalation. Long-term exposure can also cause a variety of respiratory symptoms.
white mineral oil (petroleum)	Oral (rat) TCLo: 92000 mg/kg/92D-Cont. Generally the toxicity and irritation is of low order. White oils and highly/solvent refined oils have not shown the long term risk of skin cancer that follows persistent skin contamination with some other mineral oils, due in all probability to refining that produces low content of both polyaromatics (PAH) and benz-alpha-pyrenes (BaP) For highly and severely refined distillate base oils: In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from “non-irritating” to “moderately irritating” when tested for skin and eye irritation. Testing for sensitisation has been negative. The effects of repeated exposure vary by species; in animals, effects to the testes and lung have been observed, as well as the formation of granulomas. In animals, these substances have not been found to cause reproductive toxicity or significant increases in birth defects. They are also not considered to cause cancer, mutations or chromosome aberrations. The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives; The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since: • The adverse effects of these materials are associated with undesirable components, and • The levels of the undesirable components are inversely related to the degree of processing; • Distillate base oils receiving the same degree or extent of processing will have similar toxicities; • The potential toxicity of residual base oils is independent of the degree of processing the oil receives. • The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing. Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. In comparison to unrefined and mildly refined base oils, the highly and severely refined distillate base oils have a smaller range of hydrocarbon molecules and have demonstrated very low mammalian toxicity. Testing of residual oils for mutation-causing and cancer-causing potential has shown negative results, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to their molecular size. Toxicity testing has consistently shown that lubricating base oils have low acute toxicities. Numerous tests have shown that a lubricating base oil s mutagenic and carcinogenic potential correlates with its 3-7 ring polycyclic aromatic compound (PAC) content, and the level of DMSO extractables (e.g. IP346 assay), both characteristics that are directly related to the degree/conditions of processing.
talc & white mineral oil (petroleum)	The substance is classified by IARC as Group 3: **NOT** classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
talc & isobutylene homopolymer & alpha-methylstyrene/ amylene/ piperylene copolymer & dolomite & chlorite	No significant acute toxicological data identified in literature search.

Acute Toxicity	✗	**Carcinogenicity**	✗
Skin Irritation/Corrosion	✗	**Reproductivity**	✗
Serious Eye Damage/Irritation	✗	**STOT - Single Exposure**	✗
Respiratory or Skin sensitisation	✗	**STOT - Repeated Exposure**	✗
Mutagenicity	✗	**Aspiration Hazard**	✗

Legend: ✗ *– Data either not available or does not fill the criteria for classification*
✓ *– Data available to make classification*

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Tapecoat Flangecoat	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available

talc	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	NOEC(ECx)	720h	Algae or other aquatic plants	918.089mg/l	2
	EC50	96h	Algae or other aquatic plants	7202.7mg/l	2
	LC50	96h	Fish	89581.016mg/l	2

white mineral oil (petroleum)	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96h	Fish	>10000mg/L	2
isobutylene homopolymer	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96h	Fish	>5600mg/L	4
alpha-methylstyrene/ amylene/ piperylene copolymer	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
silica amorphous, fumed, crystalline free	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
dolomite	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
chlorite	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
magnesium carbonate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	EC50	72h	Algae or other aquatic plants	>18.5mg/l	2
	NOEC(ECx)	72h	Algae or other aquatic plants	18.5mg/l	2
	LC50	96h	Fish	2120mg/l	2
coal, anthracite	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	***Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data 8. User defined data***				

for lubricating oil base stocks:
Vapor Pressure Vapor pressures of lubricating base oils are reported to be negligible. In one study, the experimentally measured vapour pressure of a solvent-dewaxed heavy paraffinic distillate base oil was 1.7 x 10exp-4 Pa . Since base oils are mixtures of C15 to C50 paraffinic, naphthenic, and aromatic hydrocarbon isomers, representative components of those structures were selected to calculate a range of vapor pressures. The estimated vapor pressure values for these selected components of base oils ranged from 4.5 x 10exp-1 Pa to 2 x 10exp-13Pa.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
isobutylene homopolymer	LOW	LOW
magnesium carbonate	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
white mineral oil (petroleum)	HIGH (LogKOW = 5.18)
isobutylene homopolymer	LOW (LogKOW = 17.14)
magnesium carbonate	LOW (LogKOW = -0.4605)

Mobility in soil

Ingredient	Mobility
isobutylene homopolymer	LOW (KOC = 35.04)
magnesium carbonate	HIGH (KOC = 1)

Other adverse effects

One or more ingredients within this SDS has the potential of causing ozone depletion and/or photochemical ozone creation.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	• Containers may still present a chemical hazard/ danger when empty. • Return to supplier for reuse/ recycling if possible. Otherwise: • If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. • Where possible retain label warnings and SDS and observe all notices pertaining to the product. • **DO NOT** allow wash water from cleaning or process equipment to enter drains. • It may be necessary to collect all wash water for treatment before disposal. • In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. • Where in doubt contact the responsible authority.

	• Recycle wherever possible or consult manufacturer for recycling options. • Consult State Land Waste Authority for disposal. • Bury or incinerate residue at an approved site. • Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO

Shipping container, transport vehicle placarding, and labeling may vary from the below information. This depends on the quantity shipped, the applicability of excepted quantity requirements, limited quantity requirements, and/or special provisions according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
talc	Not Applicable
white mineral oil (petroleum)	Not Applicable
isobutylene homopolymer	Not Applicable
alpha-methylstyrene/ amylene/ piperylene copolymer	Not Applicable
silica amorphous, fumed, crysta lline free	Not Applicable
dolomite	Not Applicable
chlorite	Not Applicable
magnesium carbonate	Not Applicable
coal, anthracite	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
talc	Not Applicable
white mineral oil (petroleum)	Not Applicable
isobutylene homopolymer	Not Applicable
alpha-methylstyrene/ amylene/ piperylene copolymer	Not Applicable
silica amorphous, fumed, crysta lline free	Not Applicable
dolomite	Not Applicable
chlorite	Not Applicable
magnesium carbonate	Not Applicable
coal, anthracite	Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

TALC IS FOUND ON THE FOLLOWING REGULATORY LISTS

- US OSHA Permissible Exposure Limits (PELs) Table Z-1
- US OSHA Permissible Exposure Limits (PELs) Table Z-3
- US ACGIH Threshold Limit Values (TLV)
- US NIOSH Recommended Exposure Limits (RELs)
- US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Carcinogens
- US - New Jersey Right to Know Hazardous Substances
- US - Massachusetts - Right To Know Listed Chemicals
- International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)
- Chemical Footprint Project - Chemicals of High Concern List
- US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2A: Probably carcinogenic to humans
- US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5
- US - Pennsylvania - Hazardous Substance List

WHITE MINERAL OIL (PETROLEUM) IS FOUND ON THE FOLLOWING REGULATORY LISTS

- US OSHA Permissible Exposure Limits (PELs) Table Z-1

- US ACGIH Threshold Limit Values (TLV)
- US DOE Temporary Emergency Exposure Limits (TEELs)
- US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic
- US - Pennsylvania - Hazardous Substance List

ISOBUTYLENE HOMOPOLYMER IS FOUND ON THE FOLLOWING REGULATORY LISTS

- US ACGIH Threshold Limit Values (TLV)
- US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Flammables
- US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
- US EPA Pesticide Chemical Search - Conventional Chemical
- US - Pennsylvania - Hazardous Substance List

ALPHA-METHYLSTYRENE/ AMYLENE/ PIPERYLENE COPOLYMER IS FOUND ON THE FOLLOWING REGULATORY LISTS

- US OSHA Permissible Exposure Limits (PELs) Table Z-1
- US OSHA Permissible Exposure Limits (PELs) Table Z-3
- US NIOSH Recommended Exposure Limits (RELs)
- International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)
- US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
- US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

SILICA AMORPHOUS, FUMED, CRYSTALLINE FREE IS FOUND ON THE FOLLOWING REGULATORY LISTS

- US OSHA Permissible Exposure Limits (PELs) Table Z-1
- US OSHA Permissible Exposure Limits (PELs) Table Z-3
- US NIOSH Recommended Exposure Limits (RELs)
- US DOE Temporary Emergency Exposure Limits (TEELs)
- US - Massachusetts - Right To Know Listed Chemicals
- International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)
- US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

DOLOMITE IS FOUND ON THE FOLLOWING REGULATORY LISTS

- US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

CHLORITE IS FOUND ON THE FOLLOWING REGULATORY LISTS

- US OSHA Permissible Exposure Limits (PELs) Table Z-1
- US OSHA Permissible Exposure Limits (PELs) Table Z-3
- US NIOSH Recommended Exposure Limits (RELs)
- International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)
- US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

MAGNESIUM CARBONATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

- US OSHA Permissible Exposure Limits (PELs) Table Z-1
- US OSHA Permissible Exposure Limits (PELs) Table Z-3
- US NIOSH Recommended Exposure Limits (RELs)
- US DOE Temporary Emergency Exposure Limits (TEELs)
- US - New Jersey Right to Know Hazardous Substances
- US - Massachusetts - Right To Know Listed Chemicals
- International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)
- US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
- US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5
- US - Pennsylvania - Hazardous Substance List

COAL, ANTHRACITE IS FOUND ON THE FOLLOWING REGULATORY LISTS

- US OSHA Permissible Exposure Limits (PELs) Table Z-1
- US OSHA Permissible Exposure Limits (PELs) Table Z-3
- US ACGIH Threshold Limit Values (TLV)
- US NIOSH Recommended Exposure Limits (RELs)
- International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)
- US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
- US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

Additional Regulatory Information

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No

Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitizatio n	No
Serious eye damage or eye irrit ation	No
Specific target organ toxicity (si ngle or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classifi ed	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

Additional Federal Regulatory Information

Not Available

US. EPCRA SECTION 313 TOXIC RELEASE INVENTORY (TRI) (40 CFR 372)

None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

None Reported

Additional State Regulatory Information

Not Available

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-I ndustrial Use	No (chlorite)
Canada - DSL	No (chlorite)
Canada - NDSL	No (talc, white mineral oil (petroleum), isobutylene homopolymer, alpha-methylstyrene/ amylene/ piperylene copolymer, silica amorphous, fume d, crystalline free, chlorite, magnesium carbonate, coal, anthracite)
China - IECSC	No (coal, anthracite)
Colombia - Colombia National I ndustrial Chemicals Inventory	No (talc, white mineral oil (petroleum), isobutylene homopolymer, alpha-methylstyrene/ amylene/ piperylene copolymer, silica amorphous, fume d, crystalline free, dolomite, chlorite, magnesium carbonate, coal, anthracite)
Europe - EINEC / ELINCS / NL P	No (alpha-methylstyrene/ amylene/ piperylene copolymer, silica amorphous, fumed, crystalline free)
Japan - ENCS	No (talc, alpha-methylstyrene/ amylene/ piperylene copolymer, dolomite, chlorite, coal, anthracite)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	TSCA Inventory 'Active' substance(s) (talc, white mineral oil (petroleum), isobutylene homopolymer, alpha-methylstyrene/ amylene/ piperylen e copolymer, dolomite, magnesium carbonate, coal, anthracite); No (silica amorphous, fumed, crystalline free, chlorite)
Taiwan - TCSI	Yes
Mexico - INSQ	No (alpha-methylstyrene/ amylene/ piperylene copolymer, chlorite)
Vietnam - NCI	No (coal, anthracite)
Russia - FBEPH	No (alpha-methylstyrene/ amylene/ piperylene copolymer, chlorite)
UAE - Control List (Banned/Res tricted Substances)	No (talc, white mineral oil (petroleum), isobutylene homopolymer, alpha-methylstyrene/ amylene/ piperylene copolymer, silica amorphous, fume d, crystalline free, dolomite, chlorite, magnesium carbonate, coal, anthracite)
Legend:	***Yes = All CAS declared ingredients are on the inventory*** ***No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.***

SECTION 16 OTHER INFORMATION

Revision Date	31/08/2026
Initial Date	28/08/2026

SDS Version Summary

Version	Issue Date	Sections Updated
0.0	01/01/0001	

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.
Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.
TEL (+61 3) 9572 4700.