We make a <u>material</u> difference		<b>Profile P</b> Cold Applied Petrolatum/Wax	Tapes		
Tapecoat Technical Data Sheet					
DESCRIPTION	Tapecoat Profile Putty is a VOC Free, cold applied, wax based putty filled with expanded polystyrene beads that is designed to fill gaps and irregular contours prior to the application of Tapecoat Envirotape. Profile Putty will protect piping and metal structures from damage and deterioration caused by corrosion at temperatures up to $95^{\circ}F$ ( $35^{\circ}C$ ). The Profile Putty encapsulates the surface in order to protect it.				
	Profile Putty comes in small contoured with a gloved han	bricks that can be applied to the sub d.	strate and		
SUBSTRATE COMPATIBILITY	Steel, Stainless Steel, Ductile Iron, Other Metals, FBE, PE, PP, Concrete				
RECOMMENDED USE	Ideal for mechanical couplings, nuts, bolts, bell and spigot joints, saddle tees, leak clamps and any area that a smoother more contoured coating surface is preferred prior to application of Envirotape.				
PRIMER	Tapecoat Profile Putty requires a primer to ensure maximum effectiveness of the system. Apply a minimum of 4 mils of Tapecoat Enviroprime using a gloved hand or by mechanical means. The Profile Putty can be applied immediately following the primer application.				
SURFACE PREPARATION	SSPC SP-2 Hand Tool Cleaning, SSPC SP-3 Power Tool Cleaning or SSPC SP-6/ NACE No. 3 Commercial Blast Cleaning				
SAFETY	Refer to Material Safety Data	a Sheet: MSDS-Profile-Putty			
APPLICATION	Refer to Application Guidelines: AG-COLD-APPLIED-PET-WAX-TAPES				

## **TYPICAL DATA**

Property	US Customary	Metric	Test Method
Color	Yellow	Yellow	
VOC Content	0 lb/gal	0 g/l	
Service Temperature Range	40°F to 95°F	5°C to 35°C	

## ORDERING INFORMATION

Slab Size	Slabs Per Case	Weight
2" x 6" x 6"	6	34# per Case

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.

TDS-Profile-Putty-REV1-Aug13

Liberty Sales & Distribution, LLC 2880 Bergey Road, Suite F, Hatfield, PA 19440 Phone: (877) 373-0118 Fax: (888) 850-3787 Email: sales@libertysales.net Web: www.libertysales.net

Chase Corporation

An ISO 9001:2008 REGISTERED COMPANY