



Technical Data Sheet

Tapecoat Rugged Wrap is a 30 mil UV resistant mesh weave fiberglass wrap that offers additional mechanical protection for protective coatings. This moisture activated non-shielding overwrap will give coatings and structures increased protection from exposure to abrasion, soil stress, frost heave and mechanical damage above and below grade.

Rugged Wrap is durable, aesthetically pleasing and available in a wide variety of colors including a full range of Safety Code Colors. These colors include Silver, White, Yellow and Black. Additional colors available upon request.

White Rugged Wrap will discolor when exposed to UV. Other colors may darken slightly after UV exposure.

Refer to Application Guidelines: AG-COLD-APPLIED-PET-WAX-TAPE

SUBSTRATE COMPATIBILITY Any protective coating. Some coatings may cause discoloration of the coating.

RECOMMENDED USE Ideal for protecting structures such as bridge crossings, riser pipes, flanges, valves, and all types of piping and metal structures.

SURFACE PREPARATION None Required. Rugged Wrap is a mechanical protective overwrap, not a corrosion preventative coating.

SAFETY Refer to Material Safety Data Sheet: MSDS-Rugged-Wrap

APPLICATION

DESCRIPTION

TYPICAL DATA

Property	US Customary	Metric	
Color	Multiple Available Multiple Available		
Cure time	<60 minutes at 70°F	<60 minutes at 21°C	
Service Temperature Range	-40°F to 350°F	-40°C to 176°C	

ORDERING INFORMATION

Roll Size	Rolls Per Case	Coverage per Case	Weight
4" x 20'	10	0.67 SQ (67 ft ²)	14# per Case
6″x30′	5	0.75 SQ (75 ft ²)	15# per Case
6″x50′	2	0.50 SQ (50 ft ²)	10# per Case
9″x50′	1	0.38 SQ (38 ft ²)	8# per Case

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.

Chase Corporation 295 University Avenue Westwood, MA 02090 Phone: 800-323-4182

Rugged Wrap

Outerwrap and Rockshield

Fax: 781-332-0701 www.chasecorp.com

An ISO 9001:2008 REGISTERED COMPANY